



अखिल भारतीय आयुर्विज्ञान संस्थान, रायपुर(छत्तीसगढ़)
All India Institute of Medical Sciences, Raipur (Chhattisgarh)
Tatibandh, GE Road,
Raipur-492 099 (CG)
www.aiimsraipur.edu.in

AIIMS/R/HS/Trauma & Emergency/2017/23-298/LPC

Date: 21/10/2017

Inviting Quotations for Purchase of (X-RAY view Box) to be used in Department of Trauma & Emergency, AIIMS Raipur.

QUOTATION NOTICE

Sealed quotations are invited from intending registered Stockist / Distributors having TIN and relevant documents for Purchase of (X-RAY view Box) to be used in **Department of Trauma & Emergency**, AIIMS Raipur. The quotation with copy of certificate of TIN & other documents should be submitted to office of **Store Officer Room No. – 51, 2nd floor Ayush Building, Gate No. 1 up to 23/10/17 before 3.00 pm**. The quotations will be opened on the same day at 3.30pm. Details of item are given as under: -

Hospital Requirement for X-RAY view Box, AIIMS, Raipur

Sr No.	Item name	Quantity required (Nos.)	Unit	Brand	Unit rate (INR)	Amount (INR)
1	<ul style="list-style-type: none">Ultra-Thin X Ray Film Illuminator using LED light.It should have a thickness of 29mm.It should be suitable for viewing 14" X 17" film.The LED Light must have a life span of more than 100000 hours.It should have easy insertion & removal of the film.It should have homogeneous illumination more than 95% and maximum intensity of over 10000 LUX.It should have an digital feather touch on-off switch along with dimmer option for each panel.It should have fully electronic continuous brightness control, with adjustment range of approximately 90%.It should be directly connectable to power supply without any external adaptor.It should have Flicker free high frequency light for reduction of eye strain.It should have a single external fuse for protection against power surge.8-10 Step Digital dimmer facility with step	7	Nos.			

	<p>up/step down intensity of 400 LUX.</p> <ul style="list-style-type: none"> • Automatic Film Sensor. • C E & ISO Certification • Warranty: 1 years. <table border="1" data-bbox="255 275 826 741"> <thead> <tr> <th colspan="2">Parameter</th> <th>Two Screen</th> </tr> </thead> <tbody> <tr> <td rowspan="2">Dimensions (mm)</td> <td>Frame (L x H x T)</td> <td>880 x 503 x 29 mm</td> </tr> <tr> <td>Viewing Area (W x H)</td> <td>735 x 440</td> </tr> <tr> <td colspan="2">Power Consumption</td> <td>30W</td> </tr> <tr> <td colspan="2">Light source</td> <td>LED</td> </tr> <tr> <td colspan="2">Power Supply Input</td> <td>AC 100 – 240V 50/60Hz</td> </tr> <tr> <td colspan="2">Brightness (LUX)</td> <td>>10000</td> </tr> <tr> <td colspan="2">Net Weight (KGS)</td> <td>8 (Approx)</td> </tr> </tbody> </table>	Parameter		Two Screen	Dimensions (mm)	Frame (L x H x T)	880 x 503 x 29 mm	Viewing Area (W x H)	735 x 440	Power Consumption		30W	Light source		LED	Power Supply Input		AC 100 – 240V 50/60Hz	Brightness (LUX)		>10000	Net Weight (KGS)		8 (Approx)					
Parameter		Two Screen																											
Dimensions (mm)	Frame (L x H x T)	880 x 503 x 29 mm																											
	Viewing Area (W x H)	735 x 440																											
Power Consumption		30W																											
Light source		LED																											
Power Supply Input		AC 100 – 240V 50/60Hz																											
Brightness (LUX)		>10000																											
Net Weight (KGS)		8 (Approx)																											
2	<ul style="list-style-type: none"> • Ultra-Thin X Ray Film Illuminator using LED light. • It should have a thickness of 29mm. • It should be suitable for viewing 14" X 17" film. • The LED Light must have a life span of more than 100000 hours. • It should have easy insertion & removal of the film. • It should have homogeneous illumination more than 95% and maximum intensity of over 10000 LUX. • It should have an digital feather touch on-off switch along with dimmer option for each panel. • It should have fully electronic continuous brightness control, with adjustment range of approximately 90%. • It should be directly connectable to power supply without any external adaptor. • It should have Flicker free high frequency light for reduction of eye strain. • It should have a single external fuse for protection against power surge. • 8-10 Step Digital dimmer facility with step up/step down intensity of 400 LUX. • Automatic Film Sensor. • C E & ISO Certification • Warranty: 1 years. 	2	Nos.																										

Parameter		Three Screen						
Dimensions (mm)	Frame (L x H x T)	1255 x 503 x 29 mm						
	Viewing Area (W x H)	1112 x 440						
Power Consumption		45W						
Light source		LED						
Power Supply Input		AC 100 – 240V 50/60Hz						
Brightness (LUX)		>10000						
Net Weight (KGS)		12 (Approx.)						
Grand Total								

Terms & Condition

1. Firm to mention Make/Brand name in their quotation.
2. Taxes, if any (Kindly mention in above table) should be clearly mentioned in the offer.
3. Document relating to registration of firm i.e. GST number and relevant document should be submitted along with quotation.
4. Products are certified from ISI/CE & ISO as applicable, the Certificate to this effect should be attached
5. Supply should be done within 15 days after Placement of PO.
6. Price should be FOR Destination basis (i.e. concerned department).
7. 100% Payment will be released after certification from concerned department.
8. **Quotation Name/No. and due date of opening must be mentioned on top of envelops.**
9. LD @ 0.5% of delayed supply per week or part of week for delay of supply of material subject to maximum up to 10% of delayed supply to be deducted.
10. AIIMS Raipur reserves the right to place order for full or part quantity to one or more firms. The AIIMS, Raipur reserves the right to increase/decrease the number of required quantity.
11. All other terms & condition as per GCC applicable.
12. Material to be delivered at **General Store, 2nd Floor AIIMS Raipur.**
13. **Validity of the quotation should be 90 days from the date of opening.**
14. **Firm to submit documentary evidence in support of their claim for GST at the time of submission of bill.**

Stores Officer (H)
AIIMS, Raipur (C.G)