

No. ~~NIA~~-03 / SE/AIIMS/2018-19

Date: 12/04/2018

NOTICE INVITING QUOTATION

Sealed Item Rates quotations for the below mentioned work are hereby invited by The Superintending Engineer on behalf of The Director, AIIMS Raipur from approved and eligible Contractors/Firms/Individuals having GST/TIN/PAN no./relevant documents along with Earnest Money in the form of Demand Draft or Pay Order or Banker's Cheque or Deposit at Call Receipt or Fixed Deposit Receipt of a Scheduled Bank (drawn/ Pledged in favour of AIIMS, Raipur) and should be submitted to the office of Project Cell, Hospital Administrative Block, Gate No-1, AIIMS Raipur up to 03:00 PM on 19th April 2018. The NIQ no, Name of Work, Name of Agency and the Designation and Address of the NIQ Authority must be mentioned over the sealed envelope. The schedule of quantity must be filled with blue ball point pen only and correction may be avoided. The bidder must self certify all the documents in the envelope. The right to reject any or all the quotations without assigning any reasons thereof shall rest with undersigned. The quotations will be opened on the same day at 3:30 pm. As per detailed below:-

S No	NAME OF WORK	EST. COST in Rupees	E.M.D in Rupees	TIME
1	Construction of kitchen platform in Resident hostel at AIIMS Raipur	48312/-	1000/-	01 Month

SCHEDULE OF QUANTITY

Sl.	Description of items	Unit	Qty	Rate	Amount
.....As PER SHEET ATTACHED.....					

Conditions:

1. Rate should be quoted inclusive of all the taxes (Nothing to be paid extra on this account). Percentage / Quantum of Tax shall be mentioned.
2. F.O.R. Project Cell, Hospital Administrative Block, Gate No-01, AIIMS Raipur.
3. The right to reject any or all the quotations without assigning any reasons and accept full or part of Quotation thereof shall rest with the Superintending Engineer.
4. Work should be completed within 01 month from the date of issue of WO.
5. As the work is to be done in running Hospital, the restrictions if any has to be obeyed by the Contractor.
6. Damage if any done/happened by the contractor then, he has to make it good as original.
7. Labour law to be obeyed by the agency.
8. The sanitary installation, Water supply items to be used in the work must be ISI Marked and approved by the Engineer In charge.
9. The CP brass Basin Mixer, angle valve used in the work must be of jaquar ,plumber,Hindware make.
10. Wash basin used in the work must be of jaquar, hindware,cera,parryware make.


Junior Engineer (Civil)
AIIMS Raipur


Superintending Engineer
AIIMS Raipur

SCHEDULE OF QUANTITY

Name of Work: Construction of kitchen platform in Resident hostel at AIIMS Raipur

S no	DSR ref no	Description of item	Qty	Unit	Rate		Amount
					In Figures	In Words	
1. BRICK WORK							
1.1	6.32.1	Brick work with clay flyash F.P.S. (non modular) brick of class designation 7.5 in superstructure above plinth level up to floor five level in :Cement mortar 1:4 (1 cement : 4 coarse sand)	0.52	Cum			
2. CEMENT CONCRETE 1:1.5:3							
2.1	4.1.2	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level: 1:1½:3 (1 Cement: 1½ coarse sand (zone-III) : 3 graded stone aggregate 20 mm nominal size).	0.051	Cum			
3. R.C.C WORK							
3.1	5.1.2	Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level : 1:1.5:3 (1 cement : 1.5 coarse sand (zone-III): 3 graded stone aggregate 20 mm nominal size).	0.16	Cum			
3.2	5.22.6	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level. Thermo-Mechanically Treated bars of grade Fe-500D or more	18	Kg			
4. Granite work							
4.1	8.2.2.2	Providing and fixing 18 mm thick gang saw cut, mirror polished, premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills, facias and similar locations of required size, approved shade, colour and texture laid over 20 mm thick base cement mortar 1:4 (1 cement : 4 coarse sand), joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. Complete at all levels. Granite of any colour and shade Area of slab over 0.50 sqm	2.1	Sqm			

4.2	8.5	Extra for providing opening of required size & shape for wash basin/ kitchen sink in kitchen platform, vanity counter and similar location in marble/ Granite/ stone work, including necessary holes for pillar taps etc. including moulding, rubbing and polishing of cut edges etc. complete.	1	Each			
4.3	8.4	Extra for fixing marble /granite stone, over and above corresponding basic item, in facia and drops of width upto 150 mm with epoxy resin based adhesive, including cleaning etc. complete.	4.1	Metre			

5. Finishing work

5.1	11.36	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.	4.75	Sqm			
-----	-------	---	------	-----	--	--	--

6. DISMANTLING AND DEMOLISHING

6.1	15.2.1	Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. Nominal concrete 1:3:6 or richer mix (i/c equivalent design mix)	0.20	Cum			
6.2	15.23.2	Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead. For thickness of tiles above 25 mm and up to 40 mm	0.1	Cum			

7 . SANITARY INSTALLATIONS

7.1	17.25.1	Providing and fixing white vitreous china wash basin including making all connections but excluding the cost of fittings : Flat back wash basin of size 630x450 mm	1	Each			
-----	---------	--	---	------	--	--	--


7.2	17.10.2 .1	Providing and fixing Stainless Steel A ISi 304 (18/8) kitchen sink as per IS: 13983 with C.I. brackets and stainless steel plug 40 mm, including painting of fittings and brackets, cutting and making good the walls wherever required : Kitchen sink without drain board : 610x510 mm bowl depth 200 mm :	1.0	Each			
7.3	17.28.2 .1	Providing and fixing P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete : Flexible pipe : 32 mm dia :	2.0	Each			
7.4	17.35.2 .1	Providing and fixing soil, waste and vent pipes : 75 mm diameter : Sand cast iron S&S pipe as per IS: 1729	9.0	Metre			
7.5	17.38.2 .1	Providing and fixing bend of required degree with access door, insertion rubber washer 3 mm thick, bolts and nuts complete : 75 mm dia : Sand cast iron S&S as per IS - 1729	2.0	Each			
7.6	17.39.2 .1	Providing and fixing plain bend of required degree : 75 mm dia : Sand cast iron S&S as per IS -1729 :	4.0	Each			
7.7	17.58.2	Providing lead caulked joints to sand cast iron/centrifugally cast (spun) iron pipes and fittings of diameter : 75 mm :	12.0	Each			
7.8	17.60.2 .1	Providing and fixing trap of self cleansing design with screwed down or hinged grating with or without vent arm complete, including cost of cutting and making good the walls and floors : 100 mm inlet and 75 mm outlet : Sand cast iron S&S as per IS - 3989 :	2.0	Each			
8 Water Supply							
8.1	18.11.1	Providing and fixing G.I. Pipes complete with G.I. fittings and clamps, i/c making good the walls etc. concealed pipe, including painting with anti corrosive bitumastic paint, cutting chases and making good the wall : 15 mm dia nominal bore :	14.0	Metre			
8.2	18.13.1	Making connection of G.I. distribution branch with G.I. main of following sizes by providing and fixing tee, including cutting and threading the pipe etc. complete : 25 to 40 mm nominal bore :	4.0	Each			

8.3	18.21.2 .1	Providing and fixing uplasticised PVC connection pipe with brass unions : 45 cm length : 15 mm nominal bore :	4.0	Each			AIIMS Raipur
8.4	18.53.1	Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 : 15mm nominal bore :	4.0	Each			
8.5	18.53A	Providing and fixing C.P. Brass extension nipple (size 15mmx50mm) of approved make and quality as per direction of Engineer-in-charge.	4.0	Each			
8.6	LMR	Providing and fixing CP Brass Basin mixer of quality & make as approved by Engineer in charge : 15 mm nominal dia	2.0	Each			
9.Drainage							
9.1	19.21.1	Making connection of drain or sewer line with existing manhole including breaking into and making good the walls, floors with cement concrete 1:2:4 mix (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) cement plastered on both sides with cement mortar 1:3 (1 cement : 3 coarse sand), finished with a floating coat of neat cement and making necessary channels for the drain etc. complete : For pipes 100 to 250 mm diameter	2.0	Each			
Total							

Total in words..... Total in Figure.....

(Signature of Contractor)


JE(c)


Superintending Engineer
Project Cell, AIIMS Raipur