

## अखिल भारतीय आयुर्विज्ञान संस्थान, रायपुर (छत्तीसगढ़) All India Institute of Medical Sciences, Raipur (Chhattisgarh)

Tatibandh, GE Road, Raipur-492 099 (CG)

www.aiimsraipur.edu.in
Date: 01-04-2019

## AIIMS/R/CS/HS/2019/9587

Inviting Quotations for Revolving Stool for Various department at AIIMS Raipur.

## **QUOTATION NOTICE**

Sealed quotations are invited from intending registered Stockist / Distributors having GST and relevant documents for Revolving Stool for Various departments at AIIMS Raipur. The quotation with copy of certificate of GST & other documents should be submitted to office of Stores Officer (Central), 2<sup>nd</sup> Floor Medical College building, Gate No-05 at AIIMS Raipur up to 10/04/19 before 03:00 pm. The quotations will be opened on the same day at 03:30pm. Details of items are given as under:-

Steel Revolving Stools:  Specifications: 1) Tabular 4 legs based 25mm×1.35mm with centre support of 32m×1.25mm tabular pipe with SS revolving top.  2) Stainless Steel set diameter 16".  3) Height adjustable from approximately 480mm to 670mm by accurately machined screw mechanism  4) Leg fitted with rubber feet.  5) Complete M.S metal structure would be treated by seven tanks process for powder coating paint i,e Digressing (1st Tank), Water rinsing (2nd Tank), Derusting by Acid (3rd Tank), Water rinsing (4th Tank), Phosphating (5th Tank), Water rinsing (6th Tank, Passivation (7th Tank) respectively with non-electrolytic deep process to produce a protective coating for	Total
Specifications:  1) Tabular 4 legs based 25mm×1.35mm with centre support of 32m×1.25mm tabular pipe with SS revolving top.  2) Stainless Steel set diameter 16".  3) Height adjustable from approximately 480mm to 670mm by accurately machined screw mechanism  4) Leg fitted with rubber feet.  5) Complete M.S metal structure would be treated by seven tanks process for powder coating paint i,e Digressing (1st Tank), Water rinsing (2nd Tank), Derusting by Acid (3rd Tank), Water rinsing (4th Tank), Phosphating (5th Tank), Water rinsing (6th Tank), Passivation (7th Tank) respectively with non-electrolytic deep process to	Amount
1) Tabular 4 legs based 25mm×1.35mm with centre support of 32m×1.25mm tabular pipe with SS revolving top.  2) Stainless Steel set diameter 16".  3) Height adjustable from approximately 480mm to 670mm by accurately machined screw mechanism  4) Leg fitted with rubber feet.  5) Complete M.S metal structure would be treated by seven tanks process for powder coating paint i,e Digressing (1st Tank), Water rinsing (2nd Tank), Derusting by Acid (3rd Tank), Water rinsing (4th Tank), Phosphating (5th Tank), Water rinsing (6th Tank, Passivation (7th Tank) respectively with non-electrolytic deep process to	
with centre support of 32m×1.25mm tabular pipe with SS revolving top.  2) Stainless Steel set diameter 16".  3) Height adjustable from approximately 480mm to 670mm by accurately machined screw mechanism  4) Leg fitted with rubber feet.  5) Complete M.S metal structure would be treated by seven tanks process for powder coating paint i,e Digressing (1st Tank), Water rinsing (2nd Tank), Derusting by Acid (3rd Tank), Water rinsing (4th Tank), Phosphating (5th) Tank), Water rinsing (6th Tank, Passivation (7th Tank) respectively with non-electrolytic deep process to	
tabular pipe with SS revolving top.  2) Stainless Steel set diameter 16".  3) Height adjustable from approximately 480mm to 670mm by accurately machined screw mechanism  4) Leg fitted with rubber feet.  5) Complete M.S metal structure would be treated by seven tanks process for powder coating paint i,e Digressing (1st Tank), Water rinsing (2nd Tank), Derusting by Acid (3rd Tank), Water rinsing (4th Tank), Phosphating (5th Tank), Water rinsing (6th Tank, Passivation (7th Tank) respectively with non-electrolytic deep process to	
2) Stainless Steel set diameter 16".  3) Height adjustable from approximately 480mm to 670mm by accurately machined screw mechanism  4) Leg fitted with rubber feet.  5) Complete M.S metal structure would be treated by seven tanks process for powder coating paint i,e Digressing (1st Tank), Water rinsing (2nd Tank), Derusting by Acid (3rd Tank), Water rinsing (4th Tank), Phosphating (5th Tank), Water rinsing (6th Tank, Passivation (7th Tank) respectively with non-electrolytic deep process to	-
3) Height adjustable from approximately 480mm to 670mm by accurately machined screw mechanism  4) Leg fitted with rubber feet.  5) Complete M.S metal structure would be treated by seven tanks process for powder coating paint i,e Digressing (1st Tank), Water rinsing (2nd Tank), Derusting by Acid (3rd Tank), Water rinsing (4th Tank), Phosphating (5th Tank), Water rinsing (6th Tank, Passivation (7th Tank) respectively with non-electrolytic deep process to	
approximately 480mm to 670mm by accurately machined screw mechanism  4) Leg fitted with rubber feet.  5) Complete M.S metal structure would be treated by seven tanks process for powder coating paint i,e Digressing (1st Tank), Water rinsing (2nd Tank), Derusting by Acid (3rd Tank), Water rinsing (4th Tank), Phosphating (5th Tank), Water rinsing (6th Tank, Passivation (7th Tank) respectively with non-electrolytic deep process to	
approximately 480mm to 670mm by accurately machined screw mechanism  4) Leg fitted with rubber feet.  5) Complete M.S metal structure would be treated by seven tanks process for powder coating paint i,e Digressing (1st Tank), Water rinsing (2nd Tank), Derusting by Acid (3rd Tank), Water rinsing (4th Tank), Phosphating (5th Tank), Water rinsing (6th Tank, Passivation (7th Tank) respectively with non-electrolytic deep process to	
accurately machined screw mechanism  4) Leg fitted with rubber feet.  5) Complete M.S metal structure would be treated by seven tanks process for powder coating paint i,e Digressing (1st Tank), Water rinsing (2nd Tank),  Derusting by Acid (3rd Tank), Water rinsing (4th Tank), Phosphating (5th Tank), Water rinsing (6th Tank, Passivation (7th Tank) respectively with non-electrolytic deep process to	
4) Leg fitted with rubber feet.  5) Complete M.S metal structure would be treated by seven tanks process for powder coating paint i,e Digressing (1st Tank), Water rinsing (2nd Tank),  Derusting by Acid (3rd Tank), Water rinsing (4th Tank), Phosphating (5th Tank), Water rinsing (6th Tank, Passivation (7th Tank) respectively with non-electrolytic deep process to	
5) Complete M.S metal structure would be treated by seven tanks process for powder coating paint i,e Digressing (1st Tank), Water rinsing (2nd Tank),  Derusting by Acid (3rd Tank), Water rinsing (4th Tank), Phosphating (5th Tank), Water rinsing (6th Tank, Passivation (7th Tank) respectively with non-electrolytic deep process to	
be treated by seven tanks process for powder coating paint i,e Digressing (1st Tank), Water rinsing (2nd Tank),  Derusting by Acid (3rd Tank), Water rinsing (4th Tank), Phosphating (5th Tank), Water rinsing (6th Tank, Passivation (7th Tank) respectively with non-electrolytic deep process to	
be treated by seven tanks process for powder coating paint i,e Digressing (1st Tank), Water rinsing (2nd Tank),  Derusting by Acid (3rd Tank), Water rinsing (4th Tank), Phosphating (5th Tank), Water rinsing (6th Tank, Passivation (7th Tank) respectively with non-electrolytic deep process to	
Tank), Water rinsing (2 <sup>nd</sup> Tank),  Derusting by Acid (3 <sup>rd</sup> Tank), Water rinsing (4 <sup>th</sup> Tank), Phosphating (5 <sup>th</sup> Tank), Water rinsing (6 <sup>th</sup> Tank,  Passivation (7 <sup>th</sup> Tank) respectively with non-electrolytic deep process to	
Derusting by Acid (3 <sup>rd</sup> Tank), Water rinsing (4 <sup>th</sup> Tank), Phosphating (5 <sup>th</sup> Tank), Water rinsing (6 <sup>th</sup> Tank,  Passivation (7 <sup>th</sup> Tank) respectively with non-electrolytic deep process to	
rinsing (4 <sup>th</sup> Tank), Phosphating (5 <sup>th</sup> Tank), Water rinsing (6 <sup>th</sup> Tank, Passivation (7 <sup>th</sup> Tank) respectively with non-electrolytic deep process to	
Tank), Water rinsing (6 <sup>th</sup> Tank, Passivation (7 <sup>th</sup> Tank) respectively with non-electrolytic deep process to	
Passivation (7 <sup>th</sup> Tank) respectively with non-electrolytic deep process to	
non-electrolytic deep process to	
produce a protective coating for	
smooth surface with gloss finish	
anticorrosive automated Powder	
coating paint of thickness 40 microns	
and oven baked for high resistance to scratch, chemical, thermal and	
mechanical stress.	
mechanical stress.	
Warranty for one year	

## नियम एवं शर्ते / Term & Conditions:-

- 1. Rate should be mentioned in words & figure both.
- 2. Taxes, if any (should be clearly mention in words & figure).
- 3. Delivery Schedule within 15 days from the date of issue of PO.
- 4. Price should be FOR Destination basis. (i.e Central Store Office, AIIMS Raipur).
- 5. LD @ 0.5% of delayed supply per week or part of week for delay of supply of material subject to maximum up to 10%. After expiry of delivery Period material cannot be accepted without the extension of delivery period.
- 6. Quotation No/Name and Due date of opening must be written on top of envelop.
- 7. GST rates applicable on your quoted item may please be confirmed. HSN code for each item shown be clearly mentioned.
- 8. Please confirm if there any change (Upward/Reduction) in your Basic Price structure. And you are also requested to pass the Input Credit as per the following Anti Profiteering Clause of GST "Upon Implementation of GST, any reduction in the rate of tax on supply of goods or service or the benefit of input tax credit shall be passed on to AIIMS Raipur by way of commensurate reduction in the prices".
- 9. In the event of increase in price, detailed justification and supporting eviden¢e may be submitted for our consideration.
- 10. The GST registration details may please be furnished.
- 11. 100% payment against receipt and acceptance of material.
- 12. Validity of offer should not be less than 90 days.
- 13. RTGS details required for payment purpose.
- 14. No part supply or part payment will be entertained.
- 15. Expenditure will be debitable to GIA-GENERAL.
- 16. Brand, Make & warranty should be clearly mentioned in offer (if required)
- 17. AIIMS Raipur reserves the right to place the order for full or part quantity to one or more firm.
- 18. The Quantity of above column is for **one unit**. However, total monetary Limit will be Rs 2,50,000.00
- 19. Supply, installation & commissioning will be done by Firm.(if applicable)
- 20. The firm should submit the compliance report of tendered material otherwise the offer will be summarily rejected.

भडार आधकारा

अ.भा.आ.सं.- रायपुर (छ.ग.)