



अखिल भारतीय आयुर्विज्ञान संस्थान, रायपुर (छत्तीसगढ़)  
**All India Institute of Medical Sciences, Raipur (Chhattisgarh)**  
Tatibandh, GE Road, Raipur-492 099 (CG)  
[www.aiimsraipur.edu.in](http://www.aiimsraipur.edu.in)

Date: 12-06-2019

**CORRIGENDUM (4)**

Tender No. : AIIMS/R/CS/MS Office/17/481/OT (Tender ID: 2019\_IMSRP\_466795\_1)

Tender for supply and installation of Bed Side Locker For hospital at AIIMS Raipur.

NIT	Existing parameters	To be read as/ Addenda
NIT Technical specification	<p>a. Size: (16 inch L x 16 inch W x 32 inch H)</p> <p>b. Framework: Mild Steel, locker structure should be made of MS tubular frame and top with SS-304 mirror finish top for better aesthetic and hygiene 18 gauge, Epoxy Powder Coated antirust type, with minimum thickness at least 60 micron.</p> <p>c. Stainless Steel Top of bed aside locker made with Stainless Steel Sheet of with thickness 18 gauge, 304 qualities. Locker must have 1.0 mm thick CRCA cabinet door provided with ventilation and cam lock. Ergonomically designed Plastic recessed handles should be provided to open the drawer and cabinet. Handles must be made of ABS and it should be recessed handle to provide to open cabinet door. Top with three sides raise edges (Top edge of the raised edges should be bent and pressed to 180 degree to prevent sharp edge) one storage Compartment and One Drawer.</p> <p>d. Top with three sides raise edges (Top edge of the raised edges should be bent and pressed to 180 degree to prevent sharp edge) one storage Compartment and One Drawer.</p> <p>e. The outside diameter of the legs of the locker should be 35-40 mm and thickness of 1.20mm – 1.50mm. f. One small Drawer under the top of bed side locker to keep small things for the user and storage compartment on the Lower Side of the unit, with the Door.</p> <p>f. Shoes made from hard rubber of uniform texture and chemically inactive to the action of mild acids. h. The manufacturer should ISO</p>	<p>a. Size: (16 inch L x 16 inch W x 32 inch H)</p> <p>b. Framework: Mild Steel, locker structure should be made of MS tubular frame and top with SS-304 mirror finish top for better aesthetic and hygiene 18 gauge, Epoxy Powder Coated antirust type, with minimum thickness at least 60 micron.</p> <p>c. Stainless Steel Top of bed aside locker made with Stainless Steel Sheet of with thickness 18 gauge, 304 qualities. Locker must have 1.0 mm thick CRCA cabinet door provided with ventilation and cam lock. Ergonomically designed Plastic recessed handles should be provided to open the drawer and cabinet. Handles must be made of ABS and it should be recessed handle to provide to open cabinet door. Top with three sides raise edges (Top edge of the raised edges should be bent and pressed to 180 degree to prevent sharp edge) one storage Compartment and One Drawer.</p> <p>d. Top with three sides raise edges (Top edge of the raised edges should be bent and pressed to 180 degree to prevent sharp edge) one storage Compartment and One Drawer.</p> <p>e. The outside diameter of the legs of the locker should be 35-40 mm and thickness of 1.20mm – 1.50mm. f. One small Drawer under the top of bed side locker to keep small things for the user and storage compartment on the Lower Side of the unit, with the Door.</p> <p>f. Shoes made from hard rubber of uniform texture and chemically inactive to the action of mild acids. h. The manufacturer should ISO certified or</p>

	<p>certified or the product should be ISI marked.</p> <p>g. The drawer as well as cabinet should be provided with Cam Lock. There need to be a gap between the drawer unit and cabinet, to keep the general items for frequent use.</p> <p>h. Color should of RAL white powder, Plastic parts in blue, SS top with buffed mirror finish for better look. Drawers and Doors should be in Blue/Sky blue colour.</p> <p>i. Firm should attached certifications as:</p> <p>I. ISO 9001: 2015 &amp; ISO 18001: 2007 (For Design, Development, Manufacturing, Marketing &amp; Sale of Furniture items) OR ISI marked product should be uploaded.</p> <p>II. Manufacture must be having BIFMA membership.</p> <p>j. Warranty should be for 5 year.</p>	<p>the product should be ISI marked.</p> <p>g. The drawer as well as cabinet should be provided with Cam Lock. There need to be a gap between the drawer unit and cabinet, to keep the general items for frequent use.</p> <p>h. Color should of RAL white powder, Plastic parts in blue, SS top with buffed mirror finish for better look. Drawers and Doors should be in Blue/Sky blue colour.</p> <p>i. Firm should attached certifications as:</p> <p>I. ISO 9001: 2015 &amp; ISO 18001: 2007 (For Design, Development, Manufacturing, Marketing &amp; Sale of Furniture items) OR ISI marked product should be uploaded.</p> <p>II. ISO 13485:2016 (for ensuring the Quality and Durability of Medical Equipment's)</p> <p>III. Manufacture must be having BIFMA membership.</p> <p>j. Warranty should be for 5 year.</p>
Page no. 10 of NIT Technical bid /Technical bid sheet	<p>k) Certificate of Manufacturer of ISO certified product should be uploaded as follows:</p> <p>a. ISO 9001: 2015 &amp; ISO 18001: 2007 (For Design, Development, Manufacturing, Marketing &amp; Sale of Furniture items) or ISI marked product should be uploaded.</p> <p>b. Manufacture must be having BIFMA membership <b>or</b></p>	<p>k) Certificate of Manufacturer of ISO certified product should be uploaded as follows:</p> <p>a. ISO 9001: 2015 &amp; ISO 18001: 2007 (For Design, Development, Manufacturing, Marketing &amp; Sale of Furniture items) or ISI marked product should be uploaded.</p> <p>b. ISO 13485:2016 (for ensuring the Quality and Durability of Medical Equipment's)</p> <p>c. Manufacture must be having BIFMA membership <b>or</b></p>
NIT Page No. 2 Critical Dates	Bid Submission End Date: 13-06-2019, 03.00 P.M.	Bid Submission End Date: 20-06-2019, 03.00 P.M.
	Bid Opening Date: 14-06-2019, 03.30 P.M.	Bid Opening Date: 21-06-2019, 03.30 P.M.

Stores Officer,  
Central Store,  
AIIMS, Raipur